



DESCRIPTION OF PARTS			
NO.	PARTS NAME	MATERIALS	QTY
1	BODY	SCS13	1
2	PLATE	SCS13 / A351 CF8	2
3	LOW SPRING	STS 316MPA(Low TORQUE)	2
4	HINGE PIN	STS 304	1
5	STOP PIN	STS 304	1
6	BODY BEARING	PTFE	2
7	PLATE BEARING	PTFE	2
8	SPRING BEARING	PTFE	3
9	CARRIER	STS 304	2
10	KEEPER PLATE	STS 316	2
11	DOWEL SCREW	STS 304	4
12	EYE BOLT	SS400	1
13	SEAT	NBR	1

SIZE	SIZE	SIZE	SIZE	QTY	WEIGHT
250A	330	146	27/4	126	3EA
					50Kg

* APPLICABLE CODE
 1) HYDRAULIC TEST : API 598
 - BODY : 1.4541Pa (HYD.)
 - SEAT : 1.08Pa (HYD.)
 2) DESIGN STANDARD : MAKER STANDARD
 3) FACE TO FACE DIMENSION : MAKER STANDARD
 4) FLANGE RATING : JIS B2220 10K F.F.

TEST	BODY	SEAT
PRESSURE (MPa)	1.48	1.08
(Sec)	120	120

* REMARK
 1. VALVE FACING : FLCD F.F (NON SEPARATED)
 2. DESIGN FLUID :

REV.	DATE	DESCRIPTION	DRAWING	REVIEWED	APPROVED
Δ	24.04.15.	FIRST ISSUE	M. S. PARK	C. H. SHIN	S. H. KANG

SOO SLING VALVE IND. CO., LTD.

DUAL CHECK VALVE DWG. (10K)
 (WATER & REMAINERS TYPE)

CONTRACTOR DWG. NO. SV-SOV1R-010-SSSSJNSL-2-01
 PROJECT NO. PAID NO. MAKER MODEL NO. REV.
 NONE NONE SVV-1R3SSJNSL 0